



Safet Data Sheet Product name: **Nylacast Nylube FG**

Revised on 23/06/2008 (in accordance with REACH regulations)

Page 1 of 4

1. Identification of the product/substance/preparation and of the company/undertaking

Identification of the product

Trade name: Nylacast Nylube FG– Nylon 6 –Food Grade

Company/manufacturer identification

Nylacast Ltd
200 Hastings Road, Leicester
LE5 0HL
United Kingdom
Tel: +44 (0) 116 276 8558
Fax: +44 (0) 116 274 1954

Advice on SDS and Technical Help

Contact: Ilija Tomic
Telephone: +44 (0) 116 276 8558
Email: ilija.tomic@nylacast.com

2. Hazards identification

Particular information pertaining specific risk for human/environment

Not classified as dangerous in accordance with EU Directive 1999/45/EC
The product does not require a hazard warning label in accordance with Directive 67/548/EC.

3. Composition/information on ingredients

Chemical characterization: Cast Polyamide 6, (Cast Nylon 6)

Description: Semi finished-product in shapes such as sheet, rods, plates, tubes and blocks.

Composition: Contains Caprolactam (CAS No.105-60-2) and solid lubricant

4. Route of exposure and first aid measures

Route of exposure

Skin Contact: Dust and particles generated during machining in contact with skin may cause irritation.
Hot or molten polymer can burn the skin.

Eye contact: Dust and fine particles generated during machining may cause mechanical irritation.
Vapor from hot/molten product can cause irritation.

Inhalation: Dust, particles and chips can be generated during machining of cast shapes.
Dust may irritate the mucous membranes of the nose and throat.
Vapor from hot/molten product can cause irritation.

Ingestion: Ingestion is not likely root of exposure, although the generated dust, particles and chips could be swallowed.

First aid procedure:

Eye Contact: Wash affected eyes for at least 15 minutes under running water with eyelids open. If irritation develop or persists, obtain medical attention.

Skin contact: Wash thoroughly with soap and water. For irritation, flush the skin with cool running water. Wash the affected area with mild soap and water. Obtain medical attention if irritation develop or persists.



Safet Data Sheet Product name: Nylacast Nylube FG

Revised on 23/06/2008 (in accordance with REACH regulations)

Page 2 of 4

If hot or molten polymer burns the skin, immerse the burned area in cold running water and obtain medical attention.

Inhalation: Remove person to a fresh air. If irritation develop or persists, obtain medical attention.

Ingestion: Use first aid techniques including coughing to remove obstruction.

If swallowed, obtain medical attention.

5. Fire-fighting measures

Suitable extinguishing media:

Water, foam, carbon dioxide

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:

In the event of fire, the following toxic vapour can be released: Carbon dioxide, carbon monoxide, Oxides of nitrogen and traces of HCN.

Special protective equipment for fire-fighters

Fire-fighters must use self-contained breathing apparatus.

6. Accidental release measures

Personal precautions

Refer to protective measures listed in section 7 and 8.

Environmental precautions

Dispose in accordance with local and national regulations. Do not dispose into the drains/surface waters/ground waters. Small particles may present a physical ingestion hazard to wildlife.

Methods for cleaning up

Sweep/shovel up. Collect dust using a suitable vacuum system. Send in suitable containers for recycling or disposal.

7. Handling and storage

Handling

No special precautions are necessary beyond normal good industrial hygiene and safety practices. Handle heavier parts either with lifting equipment or sufficient manpower.

Engineering measures

Provide suitable ventilation and dust-extraction system to minimize exposure. Use local mechanical exhaust ventilation at sources of air contamination such as processing equipment/cutting machines.

Storage

Store in a dry place away from water and high relative humidity.

8. Personal protection

Respiratory protection

Use suitable respiratory protection equipment (NIOSH approved mask) when airborne exposure limits are reached or exceeded.

Hands protection

This product does not present particular skin concern requiring special protection beyond normal good industrial hygiene and safety practices which include wearing suitable gloves to protect from abrasion and cutting.

Eye protection

**Safet Data Sheet** Product name: **Nylacast Nylube FG**

Revised on 23/06/2008 (in accordance with REACH regulations)

Page 3 of 4

Eye contact with this solid product is unlikely. However in machining areas adequate eye protection (safety goggles) should be worn to protect from small particles generated by machining.

Skin protection

Minimize skin by following good industrial hygiene and safety practices, although this product does not present significant skin concern.

9. Physical and chemical properties

Form:	Solid
Appearance:	Blocks, rods, tubes and sheets.
Colour:	Assorted colours
Odour:	Odourless
Melting temperature:	210 - 230 °C
Flash point:	Estimated to be around 370 °C
Density:	1.130 – 1.15 g/cm ³
Solubility in water:	Insoluble

10. Stability and reactivity**Conditions to avoid:**

Temperatures above recommended service temperature may cause deformation of product

Materials to avoid:

Strong acids, strong oxidizing agents and certain salts may have detrimental effect on product. Chemical resistance chart can be obtained with technical data for the material.

Hazardous decomposition products:

Thermal decomposition occurs at temperatures above melting temperature.

Combustion products are: oxides of nitrogen, carbon monoxide, carbon dioxide and hydrogen cyanide.

11. Toxicological information

Nylacast has not conducted toxicity studies on this material and no toxicological information was obtained in a reasonably extensive search of the available scientific literature.

12. Ecological information

Nylacast has not conducted environmental toxicity or biodegradable studies on this material. This material (polymer) is not classified as biodegradable.

13. Disposal considerations

Recycle or dispose in accordance with local and national regulations.

14. Transport information

This product is not defined under national/international road, rail, sea and air transport regulations as a hazardous material.



Safet Data Sheet Product name: **Nylacast Nylube FG**

Revised on 23/06/2008 (in accordance with REACH regulations)

Page 4 of 4

15. Regulatory information

This product is compliant with:

EU Directive 2002/95/EC on the restrictions of use of certain hazardous substances in electrical and electronic equipment (RoHS),

EU Directive 2002/96/EC on the restrictions of certain hazardous substances in waste electrical and electronic equipment (WEEE),

EU Directive 2003/11/EC on the restrictions of the use of PBB and PBDE fire retardants.

This product is considered not to have met any hazards category under the **section 311 and 312 of SARA Title III (Amendment Act-USA public law 99-499, Oct.17 1986)**

This is not a controlled product under the **Canadian Workplace Hazardous Materials Information System**.

16. Other information

Prepared by: Ilija Tomic – Research and Development Manager, Nylacast Ltd.

This Safety Data Sheet prepared in June 2008 in accordance with the EC Regulation Number 1907/2006 concerning the registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

While the information above is believed to be accurate and represents the best information currently available to us, Nylacast Ltd. make no warranty, expressed or implied, with respect to such information, and assume no liability resulting from its use.